

DESCRIPTION

emka[®]

Quality engineered in Germany

Supersint GM D1 5W-30

High Performance "MID SAPS" engine oil



1. APPLICATION

Fuel-economy high-performance passenger car engine oil, also specially developed to prevent early ignition (LSPI). Modern GM (Opel) gasoline engines in turbocharged/non-turbocharged passenger cars/vans and US vehicles to prevent In addition. It meets the new dexos 1™ Gen. 3 and has the performance to meet the demanding requirements of modern hybrid vehicles Suitable for the longest oil change intervals according to manufacturer specifications.

2. YOUR BENEFIT

- Prevents pre-ignition (LSPI).
- Fuel economy and low exhaust emissions.
- Outstanding engine and especially piston cleanliness.
- Very high viscosity stability and aging resistance.
- Very good protection against wear, corrosion and deposits.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- API SN (RC), API SN Plus
- ILSAC GF-6A/GF-5
- Chrysler MS-6395
- dexos 1™ Gen. 3 / GM 6094M
- Fiat 9.55535-GSX/CR1
- Ford WWS-M2C947-A/946-A/945-A/929-A
- VWC 53034



DESCRIPTION



Quality engineered in Germany

Supersint GM D1 5W-30

High Performance "MID SAPS" engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	850	Kg/m ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	62	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	11,2	mm ² /s	ASTM D7279
Viscosity Index	167		ASTM D2270
Flashpoint	>220	°C	DIN ISO 2592
Pourpoint	-36	°C	ASTM D7346

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0123500	20 Liter	0123530
205 Liter	0123510	4 x 5 Liter	0123550
60 Liter	0123520	12 x 1 Liter	0123570

