

DESCRIPTION



Supergrade LL-X LSP 5W30

FUEL saving Engine oil for FORD-Vehicles



1. APPLICATION

Supergrade LL-X LSP 5W30 is a low-friction motor oil based on HC synthetic base oils for petrol and diesel engines, especially recommended for use in newer generation Ford engines. It meets the requirements of the Ford specification M2C 913-D and is backwards compatible with the previous specifications, so it can also be used for engines with the filling specification M2C 913-A/M2C 913-B and M2C 913-C. Supergrade LL-X LSP 5W30 is a low viscosity, high shear stability motor oil that prevents deposits. It has very low friction losses, offers optimum protection against wear and enables fuel savings (CEC L-054-96) of up to 3%. An engine oil according to M2C 913-D is mandatory for use in Transit models with a 2.2 L Duratorq TDCI engine (from 04/2012)! For the other diesel engines (except KA (2009) and 1.9L TDI (VW engine) it is strongly recommended.

2. YOUR BENEFIT

- Significant fuel savings possible.
- Significant reduction in cold start wear through fast oiling.
- Excellent soot absorption and very good resistance to biodiesel (B7).

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A1/B1, A5/B5
- API SL, API CF
- Ford M2C 913-D/913-C/913-B/913-A
- Jaguar Land Rover STJLR.03.5003
- Renault RN 0700/0710
- VW 53036



DESCRIPTION



Quality engineered in Germany



Supergrade LL-X LSP 5W30

FUEL saving Engine oil for FORD-Vehicles

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	855	Kg/m ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	53	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	10,1	mm ² /s	ASTM D7279
Viscosity Index	160		ASTM D2270
Flashpoint	>240	°C	DIN ISO 2592
Pourpoint	-39	°C	ASTM D7346

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0242000	20 Liter	0242030
205 Liter	0242010	4 x 5 Liter	0242050
60 Liter	0242020	12 x 1 Liter	0242075

