

# DESCRIPTION



## Supersint LL-X F 0W30

„Low SAPS“ High-Performance low running Motor oil



### 1. APPLICATION

Supersint LL-X F 0W30 is a high-performance engine oil developed for modern petrol and diesel cars/vans/transporters according to the Euro 6/5/4 standard and especially for Ford Duratorq Euro 6 diesel engines, based on HC synthetic base oils in combination with the latest additive technology. It meets the requirements of the Ford WWSM2C950-A and mandatory for Ford Focus (from September 2014) and Mondeo (from 2015) 2.0 lt. Diesel engines required.  
It is not backward compatible with Ford engines that require an oil according to WSS-M2C913-C/-B/925-B!

### 2. YOUR BENEFIT

- Reliable cold start and fast engine oiling even at the lowest temperatures.
- SAE 0W30 viscosity grade for improved fuel efficiency and reduced CO2 emissions.
- Outstanding protection against corrosion, minimal oil consumption due to low evaporation loss.
- Stable lubricating film and best wear protection even with hot oil and extreme loads.
- Safe year-round operation because of excellent viscosity-temperature behavior and high shear stability.

### 3. TECHNICAL SPECIFICATIONS

#### Can be used with:

- ACEA C2; API SN
- Fiat 9.55535-GS1/DS1
- Ford WWS-M2C 950-A; Honda
- Jaguar Land Rover STJLR.03.5007
- VWC 53035
- Jeep; Mitsubishi; Subaru; Suzuki; Toyota



# DESCRIPTION



Quality engineered in Germany



## Supersint LL-X F 0W30

„Low SAPS“ High-Performance low running Motor oil

### 4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	847	Kg/cm <sup>3</sup>	DIN EN ISO 12185
Kin. Viscosity at 40°C	49,3	mm <sup>2</sup> /s	ASTM D7279
Kin. Viscosity at 100°C	10,0	mm <sup>2</sup> /s	ASTM D7279
Viscosity Index	195		ASTM D2270
Flashpoint	230	°C	DIN ISO 2592
Pourpoint	-48	°C	ASTM D7346
Total Base Number (TBN)	7,7	mg KOH/g	ASTM D2896

### 5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0244000	20 Liter	0244030
205 Liter	0244010	4 x 5 Liter	0244050
60 Liter	0244020	12 x 1 Liter	0244075

