

DESCRIPTION

emka[®]

Quality engineered in Germany

Supersint LL-X 0W8

Fuel economy Engine oil



1. APPLICATION

Supersint LL-X 0W8 is an extremely fuel-efficient gasoline engine oil that was specially developed for modern energy-saving and hybrid vehicles from US and Asian manufacturers. Thanks to its high-quality base oils and a first-class additive package, it optimally protects the engine against wear and deposits over the entire change interval.

2. YOUR BENEFIT

- Stable lubricating film and very good shear stability.
- Lower fuel consumption and reduced CO² emissions.
- Excellent cold start properties even at the lowest temperatures.
- Safe year-round operation due to excellent viscosity-temperature behavior.
- Very good wear and corrosion protection, reliably prevents foam formation.

3. TECHNICAL DATA

Can be used with:

- JASO GLV-1



DESCRIPTION

emka[®]

Quality engineered in Germany

Supersint LL-X 0W8

Fuel economy Engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	846	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	26,0	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	5,24	mm ² /s	ASTM D7279
Viscosity Index	140		ASTM D2270
Flashpoint	232	°C	DIN ISO 2592
Pourpoint	-45	°C	ASTM D7346
Total Base Number (TBN)	6,9	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0138600	20 Liter	0138630
1000 Liter IBC	0138601	4 x 5 Liter	0138650
205 Liter	0138610	12 x 1 Liter	0138670
60 Liter	0138620		

