

# DESCRIPTION

# emka®

Quality engineered in Germany

## Supersint LL-X 0W16

Fuel economy Engine oil



### 1. APPLICATION

Supersint LL-X 0W16 is an extremely fuel-efficient petrol engine oil that has been specially developed for modern energy-saving and hybrid vehicles from US and Asian manufacturers. With its high-quality base oils and a first-class additive package, it optimally protects the engine from wear and deposits over the entire period of the change interval.

### 2. YOUR BENEFIT

- Stable lubricating film and very good shear stability.
- Lower fuel consumption and reduced CO<sup>2</sup> emissions.
- Excellent cold start properties even at the lowest temperatures.
- Very good wear and corrosion protection, reliably prevents foaming.
- Safe all-season capability because of an excellent viscosity-temperature behavior.

### 3. TECHNICAL SPECIFICATIONS

Can be used with:

- API SP RC (Resource Conserving), API SN Plus RC
- ILSAC GF-6B
- Honda 08215-99974/08216-99974
- Honda 08232-P99S1LHE/Ultra Next/Ultra Green
- Nissan Hybrid Engine KLANM-01A04 Extra Save X Eco
- Mitsubishi DiaQueen Eco Plus
- Mitsubishi MZ102661/MZ102662
- Toyota 08880-11005



# DESCRIPTION

# emka®

Quality engineered in Germany

## Supersint LL-X 0W16

Fuel economy Engine oil



### 4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	848	Kg/cm <sup>3</sup>	DIN EN ISO 12185
Kin. Viscosity at 40°C	38,6	mm <sup>2</sup> /s	ASTM D7279
Kin. Viscosity at 100°C	7,4	mm <sup>2</sup> /s	ASTM D7279
Viscosity Index	>159		ASTM D2270
Flashpoint	>220	°C	DIN ISO 2592
Pourpoint	-48	°C	ASTM D7346
Total Base Number (TBN)	8,4	mg KOH/g	ASTM D2896

### 5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0139600	20 Liter	0139630
205 Liter	0139610	4 x 5 Liter	0139650
60 Liter	0139620	12 x 1 Liter	0139670

