

DESCRIPTION



Supersint LL FE SAE 0W-20

Fully Synthetic VW special Engine oil PAO-based



1. APPLICATION

Supersint LL FE SAE 0W-20 is a fuel-economy engine oil of the latest generation. It was specially developed for the latest 2.0 liter TFSI with 140 kW and 3.0 liter TDI CR with 160 kW engines from the VW/Audi group and may only be used for these engines with specification 508 00/509 00.

!! Not backwards compatible with specification 507 00 and older !!

A longer engine life, fuel savings (due to the extremely low viscosity class), a Efficient emission system optimization, outstanding cleanliness in the engine and optimal wear protection characterize this engine oil.

The engine oil is colored dark green to avoid confusion.

2. YOUR BENEFIT

- Longest oil intervals possible.
- Unmistakable due to dark green coloring.
- Fuel savings and CO² emission reduction.
- Due to its excellent fluidity, quick oiling in cold starts.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C6, C5
- API SP, SN Plus
- Ford WSS-M2C956-A1
- ILSAC GF-6A
- Mercedes Benz 229.72/229.71
- Porsche C20
- VW 508 00 / 509 00
- VW TL 525 77



DESCRIPTION



Quality engineered in Germany



Supersint LL FE SAE 0W-20

Fully Synthetic VW special Engine oil PAO-based

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	847	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	46,7	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	8,7	mm ² /s	ASTM D7279
Viscosity Index	166		ASTM D2270
Flashpoint	>224	°C	DIN ISO 2592
Pourpoint	-48	°C	ASTM D7346
Total Base Number (TBN)	8,5	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0126000	20 Liter	0126030
205 Liter	0126010	4 x 5 Liter	0126050
60 Liter	0126020	12 x 1 Liter	0126070

