

DESCRIPTION



Supersint RN 5W30

Smooth running Motor oil for Renault/Dacia



1. APPLICATION

Supersint RN 5W30 is a smooth-running motor oil for petrol and diesel engines with/without particle filters (OPF/DPF) and can be used if an ACEA C3, C2 motor oil is required. However, it has been specially developed for the technical requirements of Renault and Dacia car engines and also for the protection and longevity of their exhaust gas aftertreatment systems.

2. YOUR BENEFIT

- Extremely high aging resistance.
- Protects the exhaust aftertreatment system.
- Excellent cleaning properties and optimal lubrication.
- Excellent protection against wear, corrosion and foaming.

3. TECHNICAL SPECIFICATION

Can be used with:

- ACEA C3, C2;
- API SP, API SN;
- BMW Longlife-19 FE/-12 FE/-04;
- Chrysler MS-11106;
- Fiat 9.55535-S3; Ford M2C917-A;
- GM Dexos2/LL-A-025/LL-B-025;
- Mercedes Benz 229.52/229.51/229.31/226.52;
- Opel OV0401547(Dexos D)/OV0401547-D30/OV0401547-G30;
- PSA B71 2290;
- Renault RN17/RN0710/RN0700;



DESCRIPTION



Quality engineered in Germany



Supersint RN 5W30

Smooth running Motor oil for Renault/Dacia

3. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	852	Kg/m ³	ASTM D 1298
Kin. Viscosity at 40°C	72,0	mm ² /s	ASTM D 445
Kin. Viscosity at 100°C	12,1	mm ² /s	ASTM D 445
Viscosity Index	164		ASTM D 2270
Flashpoint	210	°C	ASTM D 92
Pourpoint	-45	°C	ASTM D 97

5. PACKAGING

CONTENTS	ART.NO.	CONTENTS	ART.NO.
Tankware	0233000	20 Liter	0233030
205 Liter	0233010	4 x 5 Liter	0233050
60 Liter	0233020	12 x 1 Liter	0233075

