

# DESCRIPTION



## Superpower PS-JLR 0W30

HC-Synthese „Low-SAPS“-Motorenöl



### 1. APPLICATION

Superpower PS-JLR 0W30 is an HC synthesis low-SAPS motor oil for modern petrol and diesel engines in passenger cars/SUVs and transporters (especially PSA and Jaguar Land Rover) with/without turbochargers as well as three-way catalytic converters and diesel particle filters. Due to its reduced HTHS viscosity, fuel consumption, friction and wear are minimized and emissions are reduced accordingly. Suitable for extended oil change intervals according to manufacturer specifications.

### 2. YOUR BENEFIT

- Reduced sulphated ash, phosphorus and sulfur content.
- Excellent cold start properties due to very low pour point (-51°C).
- Very good protection against wear, corrosion, deposits and foaming.
- Reliable lubricating film, very high viscosity stability and aging resistance.
- Fuel economy and low exhaust emissions under all operating conditions.
- Very good shear stability and reliable lubricating film at high operating temperatures.

### 3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C1, C2;
- Fiat 9.55535-DS1/GS-1;
- JASO DL-1;
- Jaguar Land Rover STJLR.03.5007;
- PSA B71 2312/B71 2302;



# DESCRIPTION



Quality engineered in Germany



## Superpower PS-JLR 0W30

HC-Synthese „Low-SAPS“-Motorenöl

### 4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	843	Kg/m <sup>3</sup>	DIN EN ISO 12185
Kin. Viscosity at 40°C	53,9	mm <sup>2</sup> /s	ASTM D7279
Kin. Viscosity at 100°C	10,0	mm <sup>2</sup> /s	ASTM D7279
Viscosity Index	175		ASTM D2270
Flashpoint	232	°C	DIN ISO 2592
Pourpoint	-51	°C	ASTM D7346

### 5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0246000	20 Liter	0246030
205 Liter	0246010	4 x 5 Liter	0246050
60 Liter	0246020	12 x 1 Liter	0246075

