

DESCRIPTION

emka[®]

Quality engineered in Germany

Superpower C-3 5W30

Premium HC-Synthese Engine oil



1. APPLICATION

Superpower C-3 5W30 was specially developed for cars, vans and SUVs from the manufacturers BMW, Mercedes and vehicles from the VW-Group that are equipped with exhaust aftertreatment systems. Exceptions are the in-line 5-cylinder and V10 TDI-VW engines built up to 2007, which have an oil after VW standard 506 01 must be filled. The thermal stability and the low sulphate ash content ensure particularly good piston cleanliness, regardless of the fuel.

2. YOUR BENEFIT

- Excellent cold start behavior, safe and shear-stable lubricating film.
- Excellent protection against wear, even under constant stress.
- Reduces deposits in the engine and exhaust gas turbocharger to a minimum.
- Reduction in fuel consumption.
- Extremely stable with excellent viscosity behavior.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C3, C2;
- API SP, API SN;
- BMW Longlife-04;
- Fiat 9.55535-S3;
- Mercedes Benz 229.51/229.31;
- Porsche C30;
- VW 504 00/507 00;



DESCRIPTION



Quality engineered in Germany



Superpower C-3 5W30

Premium HC-Synthese Engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	860	Kg/m ³	D 4052
Kin. Viscosity at 40°C	69,7	mm ² /s	D 445
Kin. Viscosity at 100°C	12,1	mm ² /s	D 445
Viscosity Index	173		D 2270
Pourpoint	-45	°C	D 97
Flashpoint	234	°C	D 92

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0808906	20 Liter	0808930
205 Liter	0808915	4 x 5 Liter	0808950
60 Liter	0808925	12 x 1 Liter	0808975

