

DESCRIPTION

emka®

Quality engineered in Germany

Superpower S-FP 5W30

High-performance low-friction engine oil
for vehicles of the Stellantis Group



1. APPLICATION

Superpower S-FP 5W30 is a high-performance low-friction engine oil for petrol and diesel engines with/without particulate filters (OPF/DPF)/turbo and was specially developed to meet the technical requirements of engines from the Stellantis Group (Citroen, Peugeot, DS, Opel, Vauxhall, Toyota, Fiat). It also protects against unwanted pre-ignition (LSPI) and is designed to protect and extend the life of the exhaust aftertreatment systems.

2. YOUR BENEFIT

- Extremely high resistance to aging.
- Excellent cleaning properties and optimal lubrication.
- Excellent protection against wear, corrosion and foam formation.
- Protects against premature ignition, protects the exhaust aftertreatment system.

3. TECHNICAL SPECIFICATION

Can be used with:

- ACEA C3, C2;
- API SP;
- Mercedes Benz 229.51/229.31;
- PSA B71 2297/PSA B71 2290;
- Renault RN17
- Stellantis FPW 9.55535/03;



DESCRIPTION

emka®

Quality engineered in Germany

Superpower S-FP 5W30

High-performance low-friction engine oil
for vehicles of the Stellantis Group



3. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	848	Kg/m ³	ASTM D 1298
Kin. Viscosity at 40°C	73,0	mm ² /s	ASTM D 445
Kin. Viscosity at 100°C	12,3	mm ² /s	ASTM D 445
Viscosity Index	166		ASTM D 2270
Flashpoint	>230	°C	ASTM D 92
Pourpoint	-33	°C	ASTM D 97

5. PACKAGING

CONTENTS	ART.NO.	CONTENTS	ART.NO.
Tankware	0248000	20 Liter	0248030
205 Liter	0248010	4 x 5 Liter	0248050
60 Liter	0248020	12 x 1 Liter	0248070

